



A 40-MIL, POLYETHYLENE BLEND PEEL-AND-STICK FLASHING MEMBRANE TECHNICAL DATA SHEET

MortarFlash™ Non-Asphaltic Flashing

DESCRIPTION

MortarFlash™ Non-Asphaltic Flashing is a 40-mil, polyethylene blend peel-and-stick flashing membrane with applications to:

Masonry | Concrete | Steel | Gypsum | Wood

- Tear resistant
- Will not drool when exposed to UV or heat
- Primer is not required; however, we recommend the use of a termination bar and a bead of sealant under the leading edge of the flashing
- When the use of prefabricated accessories is not feasible, MortarFlash Non-Asphaltic can be used to create inside and outside corners.

TECHNICAL DATA

UV Accelerated Weathering ASTM G154

- Mullen Burst ASTM D751 - 400 psi - 2760 kPa
- More than 90% strength retained after 2000 hours exposure

Heat Resistance

- Short Exposure - 194 F. (90 C)
- Continuous Exposure - 160 F. (71 C)
- Melting Point - 230 F (110 C)

Tensile Strength ASTM D751

- Machine Direction - 230 lbs. - 105 kg.
- Cross Direction - 210 lb. - 95 kg.
- Force Elongation 20%



Sizes & Packaging

Thickness	Roll Height	Roll Length	Rolls/Box	SF/Box	Boxes/Pallet
0.040"	9"	75'	4	225	60
	12"		3	225	60
	16"		2	200	52
	18"		2	225	60
	20"		1	125	50
	24"		1	150	50
	36"		1	225	30

AVAILABLE FLASHING COMPONENTS

Mortar Collection

- MortarNet, WallDefender, or HouseNet

Termination Bars

- PVC, T1 & T2 Stainless Steel, T1 & T2 ALuminum

Drip Edge

- Stainless Steel, Kynar-colored, Copper

Inside/Outside Corners & End Dams

- Synthetic rubber OR Thermoplastic Polyolefin
- Stainless Steel

Metal Drip Edge Corners

- Stainless Steel Pre-formed Outside 90°

Sealant

- BTL-1 Butyl

