



A 40-MIL, POLYETHYLENE BLEND PEEL-AND-STICK FLASHING MEMBRANE

DESCRIPTION

MortarFlash™ Non-Asphaltic Flashing is a 40-mil, polyethylene blend peel-and-stick flashing membrane with applications to:

Masonry | Concrete | Steel | Gypsum | Wood

- Tear resistant
- Will not drool when exposed to UV or heat
- Termination bar recommended
- Can be used to create corners in the field (or purchase our CompleteFlash® preformed corner boots and end dams)

AVAILABLE FLASHING COMPONENTS

Recommended for use with MortarFlash Non-Asphaltic

Termination Bars

- PVC - 1/8" thick, UV stabilized
- Stainless steel - 16 gauge Type 304
- Stainless steel w/ lip - 16 gauge Type 304

Drip Edge

- Stainless steel - 28 gauge Type 304
- Kynar-coated galvanized steel - 24 gauge
- Cold-rolled copper - 24 gauge

Inside/Outside Corners & End Dams

- Synthetic rubber (SR)
- TPO (Thermoplastic Polyolefin)

Metal Drip Edge Corners

- Pre-formed Outside 90°
- Adjustable 325° to 22°

MortarFlash™ Non-Asphaltic Flashing



SUBMITTAL SELECTIONS

Width (rolls are 75 ft. long)

- 9" 12" 16" 18" 20" 24" 36"
 Custom _____

Stainless Steel Drip Plate

- 1-1/2" 3" 4"

Termination Bar w/ Lip

- Stainless Steel Plastic

Termination Bar Flat

- Stainless Steel

CompleteFlash Inside/Outside Corners & End Dams

- Synthetic Rubber (SR) TPO (Thermoplastic Polyolefin)

Sealant

- BTL-1 Butyl Sealant

Specification Title: _____

Project: _____ Date: _____

Firm: _____ Phone: _____

Approval: _____ Date: _____

General Contractor: _____

Bid Date: _____

Comments: _____

